

ACR - AirConRemover



The AC-Remover ensures an easy and efficient emptying of automobile air conditioning systems (cars, trucks and busses).

With two different screw-on-hoses including a quick-lock coupling on the vehicle the used refrigerant R1234yf and R123a will be removed quickly thanks to the powerful pump. An integrated scale checks the loading capacity of the tank.

1. TECHNICAL REQUIREMENTS

- | | |
|------------------|------------------------------|
| ● Direct liquid: | 4,59 kg/min. |
| ● Direct vapore: | 0,94 kg/min. |
| ● Compressor: | 2-cylinder piston compressor |
| ● Voltage: | 220-240V, 50 Hz 1 PH |
| ● Weight: | ca. 85 kg |
| ● Dimensions: | 504x601x911 mm |
| ● Approvals: | CE / TUV-GS |

2. ORDER INFORMATION

- L-52320 ACR AirConRemover
- Optional accessories:**
- L-52303 Bottle
 - Service station for refilling on request



CENTER HEADQUARTERS

CZĘSTOCHOWA / POLAND
ROBERT ŁAPA
+48 508 032 820
robert@phucenter.pl

CENTER UK

LONDON / UNITED KINGDOM
MAGDALENA ŁAPA
+44 7497346231
magdalena@phucenter.pl

CENTER INDIA

MUMBAI / INDIA
MANOY LOKHAR
+91 7045875962
manoy@phucenter.pl