

TiltingLift TL-1



It is easy to place a car into the system. Secured by a hydraulic safety arm on the top, the car is ready to turn 70° in order to help a worker to stand upright and work on the car bottom easily.

Furthermore it is possible to lift the car up to 1750 mm. This unit offers a safe and efficient dismantling of ELVs. Once tried you will never want to work without it!



1. TECHNICAL REQUIREMENTS

- | | |
|--------------------------|-------------------|
| ● Lifting height: | up to 1750 mm |
| ● Control system: | hydraulic |
| ● Loading capacity: | 3.500 kg |
| ● Engine power: | 3 kW |
| ● Oil filling quantity: | 18/39 liter |
| ● Power supply: | 400 V |
| ● Dimension TiltingLift: | 1.5 x 2.6 x 2.5 m |
| ● Required space: | 6.0 x 6.0 x 3.5 m |



CENTER HEADQUARTERS

CZĘSTOCHOWA / POLAND
ROBERT ŁAPA
+48 508 032 820
robert@phucenter.pl

CENTER UK

LONDON / UNITED KINGDOM
MAGDALENA ŁAPA
+44 7497346231
magdalena@phucenter.pl

CENTER INDIA

MUMBAI / INDIA
MANOY LOKHAR
+91 7045875962
manoy@phucenter.pl

2. ORDER INFORMATION

- N-527511-H TiltingLift 600 (H-fork)
- N-527512-H TiltingLift 1800 (H-fork)
- N-527493-H TiltingRamp (H-fork)



CENTER HEADQUARTERS

CZĘSTOCHOWA / POLAND
ROBERT ŁAPA
+48 508 032 820
robert@phucenter.pl

CENTER UK

LONDON / UNITED KINGDOM
MAGDALENA ŁAPA
+44 7497346231
magdalena@phucenter.pl

CENTER INDIA

MUMBAI / INDIA
MANOY LOKHAR
+91 7045875962
manoy@phucenter.pl